



6 W105S Marine Generator Set

Model	Injection	Speed control	Cylinder configuration	Bore/stroke (mm)	Displacement (l)
6W105S	Mechanical	Electronic	6 in line	105X130	6.75



Customer benefits

Continuous compact power with reference performances in its category

Easy service with accessible components and unit cylinder heads

Simple technology with mechanical injection

Life cycle cost efficiency with extended mean time between overhauls (MBTO)

Rating table

Rating	Frequency	RPM	kWm	kWe	kVA
PRP	50 Hz	1500	107	100	125
PRP	50 Hz	1500	129	120	150
PRP	60 Hz	1800	116	108	135
PRP	60 Hz	1800	144	135	170

Prime running power (PRP)

- Variable load with mean power calculated on 250 running hours
- No restriction on use if mean power $\leq 75\%$ of nominal power
- Total operating time at 100% nominal power shall not exceed 500 hours per year
- 10% overload available 1 hour each 12 hours

Power definition

Standard ISO 3046/1 - 1995 (F)

Reference conditions

Ambient temperature	25 °C / 77 °F
Barometric pressure	100 kPa
Relative humidity	30%

Fuel oil

Relative density	0,840 \pm 0,005
Lower calorific power	42 700 kJ/kg
Consumption tolerances	$\pm 5\%$
Air inlet limit temperature	35 °C / 95 °F

Emissions

IMO Tier II



Standard equipment

Engine and block	Cast iron cylinder block, with replaceable cylinder liners Separate cast iron cylinder heads Replaceable valves guides and seats Steel forged crankshaft Light alloy piston with 3 high performance piston rings
Cooling system	Fresh / raw water heat exchanger with integrated thermostatic valves and expansion tank Cast iron centrifugal fresh water pump, mechanically driven Bronze self-priming raw water pump, mechanically driven
Lubrification system	Full flow screwable oil filters Fresh water cooled lube oil cooler
Fuel System	In line injection pump with flanged electronic speed governor Double wall injection bundle Duplex fuel filters Water separator
Intake air and exhaust system	Fresh water cooled exhaust gas manifold Turbo blower with insulated turbine housing
Electrical system	Voltage 24Vdc Electrical starter on flywheel crown
Generator	- 50/60Hz Frequency, 4 Pole - Insulation / Heating Class H/H - Electronic voltage regulation - Brushless excitation - IP23 Protection, Marine impregnation - Single bearing

Specific fuel consumption

PRP					75% PRP			50% PRP		
Frequency	kWe	kWm	g/kWh	I/h	kWm	g/kWh	I/h	kWm	g/kWh	I/h
50 Hz	100	107	199	25	81	203	19	53	258	16
50 Hz	120	129	194	29	97	201	23	75	228	20
60 Hz	108	116	203	28	87	207	21	58	243	16
60 Hz	136	144	200	34	109	202	26	73	218	18

Dimensions and dry weight (mm / kg)

	A	B	C	Weight
125-135 KVA	1991	1044	1130	1231
150-170 KVA	2031	1044	1130	1266

